

MATERIAL SAFETY DATA SHEET



MANUFACTURER — Dry Branch Kaolin Company
 ADDRESS — R.R. 1, P.O. Box 468 - D
 Dry Branch, Georgia 31020
 PHONE — 912/743-7474
 FAX — 912/746-0217

SECTION I, MATERIAL IDENTIFICATION

Material Trade Name: Glomax LL *Ajax SE*
 Chemical Name: Anhydrous Aluminum Silicate
 Common Name: Kaolin clay/China clay
 Physical Form: Pulverized

CAS No.
66402-68-4

HMIS RATINGS	
HEALTH HAZARD	0
FLAMMABILITY HAZARD	0
REACTIVITY HAZARD	0
MAX. PERSONAL PROTECTION	E

SECTION II, INGREDIENT AND HAZARDS	Wt.% (Approx.)	HAZARD DATA
------------------------------------	----------------	-------------

Calcined Kaolin Clay - $Al_2O_3 \cdot 2SiO_2$	99%	<u>KAOLIN</u> <u>OSHA PEL*</u> <u>ACGIH TLV*</u> Respirable 5.0 mg/m ³ 5 mg/m ³
Water	<1%	Total Dust 10.0 mg/m ³ 10 mg/m ³
*TWA for 8 hours		

SECTION III, PHYSICAL DATA

Boiling Point - Not Applicable
 Specific Gravity of Kaolin - 2.72
 Appearance & Odor - White, odorless powder
 pH 20% aqueous suspension - 4.5 - 7.0
 Solubility in water - Insoluble

SECTION IV, FIRE AND EXPLOSION DATA	LOWER	UPPER
-------------------------------------	-------	-------

Flash point - None	Not applicable	
Nonflammable, nonexplosive		

SECTION V, HEALTH HAZARD INFORMATION (See Sect. II)

Skin contact, skin absorption, eye contact, ingestion: Hazard Classification - None.
 Basis for classification: Historical. Emergency and First Aid Procedures: Eyes - flush with water. Inhalation: No acute effects. Classified as a nuisance dust by the American Conference of Governmental and Industrial Hygienists. Exposure to large quantities of kaolin over several years without use of a dust mask could affect respiratory function. **See Am. Rev. Respir. Dis.** 1983; 127:215-220; 231-235; 141-142.
 No crystalline silica detected using the recommended NIOSH test method 7500.

SECTION VI, REACTIVITY DATA

Conditions contributing to instability - None, inert and nonreactive.
Incompatibility - None, inert and nonreactive.
Hazardous Decomposition Products - None, inert and nonreactive.
Conditions Contributing to Hazardous Polymerization - None, inert and nonreactive.

SECTION VII, SPILL, LEAK, AND DISPOSAL PROCEDURES

Aquatic toxicity: Insignificant. TLM 96: over 1000 ppm.
Waste Disposal Method: Landfill
Steps to be taken if material is released or spilled: Vacuum dust. If sweeping, use dust suppressant.
Neutralizing chemicals: None required. Material is inert.

SECTION VIII, SPECIAL PROTECTION INFORMATION

Ventilation requirements: Same as for any nuisance dust.
Specific Personal Protective Equipment: Respiratory face mask suggested for dusty conditions.
MSHA Model 8710 or NIOSH approved mechanical filter type respirator may be used.
Eye - not required; clear plastic shield may be used as convenience item.
Gloves or other protective clothing - not required.

SECTION IX, SPECIAL PRECAUTIONS AND COMMENTS

Aqueous slurry is slippery; care should be exercised when walking on spills on floors or concrete pads.
Additional Regulatory Concerns: FDA - Generally recognized as safe - 21 CFR 186.1256; TSCA - Product, a naturally occurring substance, is listed in Initial Inventory, Vol. 1, Appendix A, CAS No. 1332-58-7
DOT classification - Not restricted

Although reasonable care has been taken in the preparation of the information contained herein, Dry Branch Kaolin Co. extends no warranties, makes no representation and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.

DATE PREPARED 8/25/87

REVISED 1/1/91