

MATERIAL SAFETY
DATA SHEET

CHEMICATOR PRODUCTS, INC.
P.O. BOX 2385
HUNTINGTON PARK, CA 90255-2385
(800) 421-4822

24-HOUR
EMERGENCY
TELEPHONE
800 255-3924

PLASTILUBE, 55 DM.

PRODUCT ID NO.: 51PLB000A

PAGE: 1

FOR: LAGUNA CLAY COMPANY
14400 LOOMIS AVE.

EFFECTIVE DATE: 05/17/98

PRODUCT ID NO.: 51PLB000A

BILL OF LADING NO.: 070967

CITY OF INDUSTRY CA 91744

BILL OF LADING DATE: 04/19/01

DATE PREPARED: 04/19/01

=====
This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200
(The Hazard Communication Standard)

=====
SECTION I - PRODUCT IDENTIFICATION

PRODUCT DESCRIPTION: PLASTILUBE, 55 DM.

D.O.T. PROPER SHIPPING NAME: NOT CLASSIFIED AS HAZARDOUS

NFPA CODES: HEALTH - 0 FLAMMABILITY - 0 CORROSIVE - 0 REACTIVITY - 0

=====
SECTION II - COMPONENTS

NO HAZARDOUS INGREDIENTS PRESENT

"*" If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

=====
SECTION III - PHYSICAL DATA

BOILING POINT FOR PRODUCT: >220 F.

VAPOR PRESSURE FOR PRODUCT: N/D

VAPOR DENSITY FOR PRODUCT: N/D

SPECIFIC GRAVITY: 1.04

V.O.C.(GRAMS PER LITER): 0

WATER SOLUBILITY: COMPLETE

APPEARANCE: LIGHT YELLOW LIQUID

pH: 9.0

=====
SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT(N/A): NON FLAMMABLE

EXPLOSIVE LIMIT (PRODUCT): LOWER - N/A UPPER - N/A

FIRE & EXPLOSION HAZARDS: Keep containers cool. Use equipment or shielding required to protect personnel against bursting, rupturing, venting containers.

FIRE FIGHTING EQUIPMENT: At elevated temperatures (above 120 F) containers may vent, rupture, or burst.

EXTINGUISHING MEDIA: Foam Dry Chemical, Carbon Dioxide.

CHEMICATOR PRODUCTS, INC.
P.O. BOX 2385
HUNTINGTON PARK, CA 90255-2385
(800) 421-4822

24-HOUR
EMERGENCY
TELEPHONE
800 255-3924

MATERIAL SAFETY
DATA SHEET

PLASTILUBE, 55 DM.

PRODUCT ID NO.: 51PLB000A

PAGE: 2

=====
SECTION IV - FIRE AND EXPLOSION DATA (CONTINUED) =====

=====
SECTION V - HEALTH HAZARD DATA =====

SEC05.10

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVER EXPOSURE: Irritation to skin and eyes.

EMERGENCY FIRST AID PROCEDURES:

SKIN: Wash with soap and water.

EYE: Flush with water for at least 15 minutes.

INHALATION: Remove to fresh air. See a physician if irritation persist.

ORAL: Call a physician. Do not induce vomiting.

ADDITIONAL: Contact with eyes will be painful and irritating.

Prolonged or repeated contact with skin may cause irritation. Mist

caused by manufacturing operations may irritate the nasal passages.

=====
SECTION VI - REACTIVITY DATA =====

INCOMPATIBILITY: Strong Oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Sulfur dioxide, Hydrogen Sulfide,
Nitrous Oxides and Ammoniacal Vapors.

POLYMERIZATION: Will not occur.

=====
SECTION VII - SPILL OR LEAK PROCEDURES =====

SEC07.10

SPILL PROCEDURES: Pick up free material for recycle/disposal.

WASTE DISPOSAL:

Disposal should be in compliance with Federal, State and local laws.

=====
SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED =====

SEC08.10

VENTILATION PROCEDURE: Use adequate ventilation

GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended.

RESPIRATORY PROTECTION: When applicable, wear a NIOSH approved respirator
appropriate for the vapor or mist concentration at
the point of use.

EYE PROTECTION: Safety glasses.

OTHER PROTECTION: None

=====
SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS =====

SEC09.10

STORAGE AND HANDLING PRECAUTIONS: Store in a cool, dry well-ventilated
place away from incompatible materials. Keep container tightly closed

MATERIAL SAFETY
DATA SHEET

CHEMICATOR PRODUCTS, INC.
P.O. BOX 2385
HUNTINGTON PARK, CA 90255-2385
(800) 421-4822

24-HOUR
EMERGENCY
TELEPHONE
800 255-3924

PLASTILUBE, 55 DM.

PRODUCT ID NO.: 51PLB000A

PAGE: 3

==== SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS (CONTINUED) ==
when not in use. Do not use pressure to empty container. Wash thoroughly
after handling. Do not get in eyes, on skin, or on clothing. Store in
original containers only at temperatures below 85 deg. f. Do not store
near acids, oxidizable materials, organics.

OTHER PRECAUTIONS: Containers, even those that have been emptied, will
retain product residue and vapors. Always obey hazard warnings and handle
empty containers as if they were full. Do not mix this product with other
cleaning agents. It is a violation of federal law to use this product in a
manner inconsistent with its labeling.

SPECIAL PRECAUTIONS: Minimal handling temperature should be maintained. Do
not ingest.

===== ADDITIONAL COMMENTS =====

The above information is based on the data of which we are aware and is
believed to be correct as of the date hereof. Since the information
contained herein may be applied under conditions beyond our control and
with which we may be unfamiliar and since data made available subsequent
to the date hereof may suggest modification of the information, we do not
assume any responsibility for the results of its use. This information is
furnished upon condition that the person receiving it shall make his own
determination of the suitability of the material for his particular purpose.